

Appendix A - Extract from Technical Guidance to the NPPF

Flood risk

As set out in the National Planning Policy Framework, inappropriate development in areas at risk of flooding should be avoided by directing development away from areas at highest risk, but where development is necessary, making it safe without increasing flood risk elsewhere. For these purposes:

- “areas at risk of flooding” means land within Flood Zones 2 and 3; or land within Flood Zone 1 which has critical drainage problems and which has been notified to the local planning authority by the Environment Agency;
- “flood risk” means risk from all sources of flooding - including from rivers and the sea, directly from rainfall on the ground surface and rising groundwater, overwhelmed sewers and drainage systems, and from reservoirs, canals and lakes and other artificial sources.

The Sequential and Exception Tests

As set out in the National Planning Policy Framework, the aim of the Sequential Test is to steer new development to areas with the lowest probability of flooding. The flood zones (see table 1) are the starting point for this sequential approach. Zones 2 and 3 are shown on the flood map¹ with Flood Zone 1 being all the land falling outside Zones 2 and 3. These flood zones refer to the probability of sea and river flooding only, ignoring the presence of existing defences.

Strategic Flood Risk Assessments (see paragraphs 7-8) refine information on the probability of flooding, taking other sources of flooding and the impacts of climate change (see paragraphs 11-15) into account. They provide the basis for applying the Sequential Test, on the basis of the flood zones in table 1. Where table 1 indicates the need to apply the Exception Test (as set out in the National Planning Policy Framework), the scope of a Strategic Flood Risk Assessment will be widened to consider the impact of the flood risk management infrastructure on the frequency, impact, speed of onset, depth and velocity of flooding within the flood zones considering a range of flood risk management maintenance scenarios. Where a Strategic Flood Risk Assessment is not available, the Sequential Test will be based on the Environment Agency flood zones.

The overall aim should be to steer new development to Flood Zone 1. Where there are no reasonably available sites in Flood Zone 1, local planning authorities allocating land in local plans or determining planning applications for development at any particular location should take into account the flood risk vulnerability of land uses (see table 2) and consider reasonably available sites in Flood Zone 2, applying the Exception Test if required (see table 3). Only where there are no reasonably available sites in Flood Zones 1 or 2 should the suitability of sites in Flood Zone 3 be considered, taking into account the flood risk vulnerability of land uses and applying the Exception Test if required.

¹ To access the flood map, see the Environment Agency's website at:
<https://flood-warning-information.service.gov.uk/map>

Table 1: Flood zones

(Note: These flood zones refer to the probability of river and sea flooding, ignoring the presence of defences)

Zone 1 - low probability

Definition

This zone comprises land assessed as having a less than 1 in 1,000 annual probability of river or sea flooding (<0.1%).

Appropriate uses

All uses of land are appropriate in this zone.

Flood risk assessment requirements

For development proposals on sites comprising one hectare or above the vulnerability to flooding from other sources as well as from river and sea flooding, and the potential to increase flood risk elsewhere through the addition of hard surfaces and the effect of the new development on surface water run-off, should be incorporated in a flood risk assessment. This need only be brief unless the factors above or other local considerations require particular attention.

Policy aims

In this zone, developers and local authorities should seek opportunities to reduce the overall level of flood risk in the area and beyond through the layout and form of the development, and the appropriate application of sustainable drainage systems².

Zone 2 - medium probability Definition This zone comprises land assessed as having between a 1 in 100 and 1 in 1,000 annual probability of river flooding (1% – 0.1%), or between a 1 in 200 and 1 in 1,000 annual probability of sea flooding (0.5% – 0.1%) in any year. Appropriate uses Essential infrastructure and the water-compatible, less vulnerable and more vulnerable uses, as set out in table 2, are appropriate in this zone. The highly vulnerable uses are <i>only</i> appropriate in this zone if the Exception Test is passed. Flood risk assessment requirements All development proposals in this zone should be accompanied by a flood risk assessment. Policy aims In this zone, developers and local authorities should seek opportunities to reduce the overall level of flood risk in the area through the layout and form of the development, and the appropriate application of sustainable drainage systems.
Zone 3a - high probability Definition This zone comprises land assessed as having a 1 in 100 or greater annual probability of river flooding (>1%), or a 1 in 200 or greater annual probability of flooding from the sea (>0.5%) in any year. Appropriate uses The water-compatible and less vulnerable uses of land (table 2) are appropriate in this zone. The highly vulnerable uses should not be permitted in this zone. The more vulnerable uses and essential infrastructure should only be permitted in this zone if the Exception Test is passed. Essential infrastructure permitted in this zone should be designed and constructed to remain operational and safe for users in times of flood. Flood risk assessment requirements All development proposals in this zone should be accompanied by a flood risk assessment. Policy aims In this zone, developers and local authorities should seek opportunities to: • reduce the overall level of flood risk in the area through the layout and form of the development and the appropriate application of sustainable drainage systems; • relocate existing development to land in zones with a lower probability of flooding; and • create space for flooding to occur by restoring functional floodplain and flood flow pathways and by identifying, allocating and safeguarding open space for flood storage.
Zone 3b - the functional floodplain Definition This zone comprises land where water has to flow or be stored in times of flood. Local planning authorities should identify in their Strategic Flood Risk Assessments areas of functional floodplain and its boundaries accordingly, in agreement with the Environment Agency. The identification of functional floodplain should take account of local circumstances and not be defined solely on rigid probability parameters. But land which would flood with an annual probability of 1 in 20 (5%) or greater in any year, or is designed to flood in an extreme (0.1%) flood, should provide a starting point for consideration and discussions to identify the functional floodplain. Appropriate uses Only the water-compatible uses and the essential infrastructure listed in table 2 that has to be there should be permitted in this zone. It should be designed and constructed to: • remain operational and safe for users in times of flood; • result in no net loss of floodplain storage; • not impede water flows; and • not increase flood risk elsewhere. Essential infrastructure in this zone should pass the Exception Test. Flood risk assessment requirements All development proposals in this zone should be accompanied by a flood risk assessment. Policy aims In this zone, developers and local authorities should seek opportunities to: • reduce the overall level of flood risk in the area through the layout and form of the development and the appropriate application of sustainable drainage systems; • relocate existing development to land with a lower probability of flooding.

[Table 2: Flood risk vulnerability classification](#)

Essential infrastructure • Essential transport infrastructure (including mass evacuation routes) which has to cross the area at risk. • Essential utility infrastructure which has to be located in a flood risk area for operational reasons, including electricity generating power stations and grid and primary substations; and water treatment works that need to remain operational in times of flood. • Wind turbines.
--

Highly vulnerable • Police stations, ambulance stations and fire stations and command centres and telecommunications installations required to be operational during flooding. • Emergency dispersal points. • Basement dwellings. • Caravans, mobile homes and park homes intended for permanent residential use³. • Installations requiring hazardous substances consent⁴. (Where there is a demonstrable need to locate such installations for bulk storage of materials with port or other similar facilities, or such installations with energy infrastructure or carbon capture and storage installations, that require coastal or water-side locations, or need to be located in other high flood risk areas, in these instances the facilities should be classified as “essential infrastructure”)⁵.
More vulnerable • Hospitals. • Residential institutions such as residential care homes, children’s homes, social services homes, prisons and hostels. • Buildings used for dwelling houses, student halls of residence, drinking establishments, nightclubs and hotels. • Non-residential uses for health services, nurseries and educational establishments. • Landfill and sites used for waste management facilities for hazardous waste⁶. • Sites used for holiday or short-let caravans and camping, subject to a specific warning and evacuation plan.⁷
Less vulnerable • Police, ambulance and fire stations which are not required to be operational during flooding. • Buildings used for shops, financial, professional and other services, restaurants and cafes, hot food takeaways, offices, general industry, storage and distribution, non-residential institutions not included in “more vulnerable”, and assembly and leisure. • Land and buildings used for agriculture and forestry. • Waste treatment (except landfill and hazardous waste facilities). • Minerals working and processing (except for sand and gravel working). • Water treatment works which do not need to remain operational during times of flood. • Sewage treatment works (if adequate measures to control pollution and manage sewage during flooding events are in place).
Water-compatible development • Flood control infrastructure. • Water transmission infrastructure and pumping stations. • Sewage transmission infrastructure and pumping stations. • Sand and gravel working. • Docks, marinas and wharves. • Navigation facilities. • Ministry of Defence defence installations. • Ship building, repairing and dismantling, dockside fish processing and refrigeration and compatible activities requiring a waterside location. • Water-based recreation (excluding sleeping accommodation). • Lifeguard and coastguard stations. • Amenity open space, nature conservation and biodiversity, outdoor sports and recreation and essential facilities such as changing rooms. • Essential ancillary sleeping or residential accommodation for staff required by uses in this category, <i>subject to a specific warning and evacuation plan</i>.

Notes to Table 2:

- This classification is based partly on Department for Environment, Food and Rural Affairs and Environment Agency research on *Flood Risks to People (FD2321/TR2)*⁸ and also on the need of some uses to keep functioning during flooding.
- Buildings that combine a mixture of uses should be placed into the higher of the relevant classes of flood risk sensitivity. Developments that allow uses to be distributed over the site may fall within several classes of flood risk sensitivity.
- The impact of a flood on the particular uses identified within this flood risk vulnerability classification will vary within each vulnerability class. Therefore, the flood risk management infrastructure and other risk mitigation measures needed to ensure the development is safe may differ between uses within a particular vulnerability classification.

[Table 3: Flood risk vulnerability and flood zone 'compatibility'](#)

Flood Risk Vulnerability classification (see Table 2)		Essential Infrastructure	Water compatible	Highly Vulnerable	More Vulnerable	Less Vulnerable
Flood Zone (see Table 1)	Zone 1	✓	✓	✓	✓	✓
	Zone 2	✓	✓	Exception Test required	✓	✓
	Zone 3a	Exception Test required	✓	✗	Exception Test required	✓
	Zone 3b 'Functional Floodplain'	Exception Test required	✓	✗	✗	✗

Key: ✓ Development is appropriate.
✗ Development should not be permitted.

[Notes to Table 3:](#)

This table does not show:

- the application of the Sequential Test which guides development to Flood Zone 1 first, then Zone 2, and then Zone 3;
- flood risk assessment requirements; or
- the policy aims for each flood zone.

[Flood risk assessment](#)

Properly prepared assessments of flood risk will inform the decision-making process at all stages of development planning. A Strategic Flood Risk Assessment is a study carried out by one or more local planning authorities to assess the risk to an area from flooding from all sources, now and in the future, taking account of the impacts of climate change, and to assess the impact that changes or development in the area will have on flood risk. It may also identify, particularly at more local levels, how to manage those changes to ensure that flood risk is not increased. A site-specific flood risk assessment is carried out by, or on behalf of, a developer to assess the risk to a development site and demonstrate how flood risk from all sources of flooding to the development itself and flood risk to others will be managed now, and taking climate change into account. There should be iteration between the different levels of flood risk assessment.

Strategic Flood Risk Assessment

As set out in the National Planning Policy Framework, Local Plans should be supported by Strategic Flood Risk Assessment. The Strategic Flood Risk Assessment should be prepared in consultation with the Environment Agency, local planning authorities' own functions of emergency response and drainage authority under the Land Drainage Act 1991, and where appropriate, internal drainage boards. Initially the Strategic Flood Risk Assessment will be used to refine information on the areas that may flood, taking into account other sources of flooding and the impacts of climate change, in addition to the information on the flood map. Local planning authorities should use the Strategic Flood Risk Assessment to inform their knowledge of flooding, refine the information on the flood map and determine the variations in flood risk from all sources of flooding across and from their area. These should form the basis for preparing appropriate policies for flood risk management for these areas. The Strategic Flood Risk Assessment should be used to inform the sustainability appraisal (incorporating the Strategic Environmental Assessment Directive) of local development documents, and will provide the basis from which to apply the Sequential Test and Exception Test in the development allocation and development control process.

Where local planning authorities have been unable to allocate all proposed development and infrastructure in accordance with the Sequential Test, taking account of the flood vulnerability category of the intended use, it will be necessary to increase the scope of the Strategic Flood Risk Assessment to provide the information necessary for application of the Exception Test. This should, additionally, consider the beneficial effects of flood risk management infrastructure in generally reducing the extent and severity of flooding when compared to the flood zones on the flood map. The increased scope of the Strategic Flood Risk Assessment will enable the production of mapping showing flood outlines for different probabilities, impact, speed of onset, depth and velocity variance of flooding taking account of the presence and likely performance of flood risk management infrastructure.

Site-specific flood risk assessment

As set out in the National Planning Policy Framework, local planning authorities should only consider development in flood risk areas appropriate where informed by a site-specific flood risk assessment. This should identify and assess the risks of all forms of flooding to and from the development and demonstrate how these flood risks will be managed so that the development remains safe throughout its lifetime, taking climate change into account. Those proposing developments should take advice from the emergency services when producing an evacuation plan for the development as part of the flood risk assessment.

Minor developments¹⁰ are unlikely to raise significant flood risk issues unless they would:

- have an adverse effect on a watercourse, floodplain or its flood defences;
- would impede access to flood defence and management facilities; or
- where the cumulative impact of such developments would have a significant effect on local flood storage capacity or flood flows.

Managing residual flood risk

Residual risks are those remaining after applying the sequential approach and taking mitigating actions. It is the responsibility of those planning development to fully assess flood risk, propose measures to mitigate it and demonstrate that any residual risks can be safely managed. Flood resistance and resilience measures should not be used to justify development in inappropriate locations.

⁹ The Environment Agency provides 'standing advice' on flood risk – see the Agency's website at: <http://www.environment-agency.gov.uk/research/planning/82584.aspx>. Applicants for planning permission will find this advice helpful when preparing a site-specific flood risk assessment for, and before designing, a lower risk development (and for ensuring extensions or alterations are designed and constructed to conform to any flood protection already incorporated in the property and include flood resilience measures in the design). The Agency also provides standing advice to enable local planning authorities to clearly identify the type of planning applications on which they should consult the Agency, and to make decisions on low risk applications where flood risk is an issue, without directly consulting the Agency for an individual response.

¹⁰ Minor development means: - Minor non-residential extensions: industrial/commercial/leisure etc. extensions with a footprint less than 250sqm.

- Alterations: development that does not increase the size of buildings e.g. alterations to external appearance. -
Householder development: e.g. sheds, garages, games rooms etc. within the curtilage of the existing dwelling in addition to physical extensions to the existing dwelling itself. This definition excludes any proposed development that would create a separate dwelling within the curtilage of the existing dwelling e.g. subdivision of houses into flats.

Flood resilience and resistance

The relative benefits of resilient and resistant construction have been assessed both through risk assessment and the real time testing of model forms of construction. Resilient construction is favoured because it can be achieved more consistently and is less likely to encourage occupiers to remain in buildings that could be inundated by rapidly rising water levels.

Flood-resilient buildings are designed to reduce the consequences of flooding and facilitate recovery from the effects of flooding sooner than conventional buildings. This may be achieved through the use of water-resistant materials for floors, walls and fixtures and the siting of electrical controls, cables and appliances at a higher than normal level. The lower floors of buildings in areas at medium and high probability of flooding should be reserved for uses consistent with Table 1. If the lowest floor level is raised above the predicted flood level, consideration must be given to providing access for those with restricted mobility. In considering appropriate resilience measures, it will be necessary to plan for specific circumstances and have a clear understanding of the mechanisms that lead to flooding and the nature of the flood risk by undertaking a flood risk assessment.

Flood-resistant construction can prevent entry of water or minimise the amount of water that may enter a building where there is flooding outside. This form of construction should be used with caution and accompanied by resilience measures, as effective flood exclusion may depend on occupiers ensuring some elements, such as barriers to doorways, are put in place and maintained in a good state. Buildings may also be damaged by water pressure or debris being transported by flood water. This may breach flood-excluding elements of the building and permit rapid inundation. Temporary and demountable defences are not normally appropriate for new developments.